



NOVAMIX 201

The effective reply to all needs in the field of welding



The Power Source INVERTER **NOVAMIX 201** thanks to its weight of Kg 13.5 and its reduced dimensions is ideal to the most varied requirements of the welding market.

The 3 welding process of which has (MIG/MAG – TIG - MMA) allow to solve any problem in the field of welding.

Thanks to the reverse polarity device it is possible to weld using cored wires without GAS.

It mounts a coil 5 kg and thanks to the synergic programs the use is very easy and simplified and therefore suitable for low-skilled operators too.

- INVERTER Technology
- Energy Saving
- Polarity Reverse
- Arc - Force Adjustment
- Slope down Adjustment
- Electronic Inductance Adjustment
- Welding Process Switch
- 2T or 4T switch
- Digital Display Ampere - Volt
- Burn - Back adjustment
- Welding Programs selector



Applications

Metal Industry in general
Buildings
Constructions
Petrol Industry
Military industry
Food industry
Earthmoving industry
Sheet metal working



Accessories

Technical data NOVAMIX 201

Earth cable 25 mm ² Mt. 3.0	3.610.105	Power, singlephase	230 V
Torch MIG – MAG AS.26 Mt.3 - Air	2.500.003	Fuse	40 A
Torch MIG – MAG AS.26 Mt.4 - Air	2.500.004	Max Absorption	37 A
Torch SINCOMIG 25 Mt.4 - Air	8.514.000	Noises	< 70 dB
Torch SINCOTIG 17 Mt.4	8.614.000	Max Power output	8,5 KVA
Pressure ARGON Reducer	5.790.913	Duty cycle 100%	90 A
Pressure O2 Reducer	5.790.916	Duty cycle 60%	115 A
		Duty cycle 25%	200 A
		Open Circuit V	63 V
		Welding range TIG	10 - 200 A
		Welding range MMA	10-170 A
		Welding range MIG	200 A
		CE Standards	EN 60974-1 - 5 – 10
		Application Class	S
		Insulating Class	F
		Protection Class	IP23S
		Cooling	AF
		Operating Temperature	- 10 + 40 ° C
		Wire Diameters	
		Steel	0.6 – 1 mm
		Stainell Steel	0.8 – 1 mm
		Aluminium	1 mm
		Electrodes diam.	1 – 4 mm
		Wire speed	2 – 20 Mt./min
		Wire coils	5 Kg
		Dimensions, mm (L x B x H)	480 x 210 x 400
		Weight, Kg	13.5

Items number

M.001.152

Generator NOVAMIX 201



Sincosald s.r.l. - Via della fisica 26/28 - 20864 - Agrate Brianza (MB)
Tel +39 039 641171 – Fax +39 039 6057122

E-MAIL export@sincosald.it



www.sincosald.it